

Positive list of permissible matrices for the establishment of biochar C-sinks (H/Corg < 0.4)

v3_12: Latest update 28.07.2025

For biochars presenting an H to Corg ratio below 0.40. A new persistence evaluation system based on advanced analysis is in preparation. The latter mainly concerns the proportions of the PAC and SPC fractions. For biochars with an H to Corg ratio above and equal to 0.40, please refer to the indications in the standard.

Origin	Matrix	ID	Controlling period in years	Diffuse C-sink authorized	Leakage margin to be deduced before registration	C remaining during temporary C-sink	C remaining after > 1000 y	SPC fraction with MRT of 50 years	Conditions	EBC-FeedPlus	EBC-Feed	EBC-AgroOrganic	EBC-Agro	EBC-Urban	EBC-Consumer-Materials	EBC-BasicMaterials	WBC Premium	WBC Agro	WBC Materials	Global Artisan C-Sink
Biological Matrix - For all packaging and delivering units containing biochar with > 1 t CO ₂ e, the biochar and its C-sink matrix must be tracked to the location of soil application.	Compost	B-01		✓			75%	25%	The use of compost as soil amendment must be proven. When used to produce potting soil, it has to be declared as matrix B-09.	✓		✓	✓	(✓)*			✓	✓		✓
	Solid Manure	B-02		✓			75%	25%	The use as soil amendment must be proven. It must not be pyrolysed, combusted. If the manure is treated by anaerobic digestion, non combusive use of the solid digestate must be guaranteed.	✓		✓	✓	(✓)*			✓	✓		✓
	Liquid Manure	B-03		✓			75%	25%	If the manure is treated by anaerobic digestion, non combusive use of the solid digestate must be guaranteed.	✓		✓	✓	(✓)*			✓	✓		✓
	Anaerobic Digestate	B-04		✓			75%	25%	The use as soil amendment must be proven, must not used as feedstock for pyrolysis.	✓		✓	✓	(✓)*			✓	✓		✓
	Biochar Based Fertilizer	B-06		✓			75%	25%	The fertilizer does not reduce the permanence but biochar may increase emissions during manufacturing and storage. A GHG balance of the production must be provided.	✓		✓	✓	(✓)*			✓	✓		✓
	Animal feed	B-07		✓			75%	25%	Only livestock feed with guaranteed end-of-life as soil amendment. Horse and chicken manure are often used for energetic purposes, which must be excluded. Pet feed products are generally excluded as pet excreta end up mainly in waste treatment plants.	✓	✓						✓	not recommended		
	Seed coating	B-08		✓	10%		75%	25%	An accounting for waste seed management must be provided and deduced from C-sink. 10% margin because expired seeds are often combusted.	✓		✓	✓				✓	✓		✓
	Potting soil / growing media / substrates for horticulture	B-09		✓	<> 20%		75%	25%	Life cycle data and statistics must prove that the end of life is in soil (e.g., via composting) for a relevant share of the total volume produced. This share defines the security margin.	✓		✓	✓				✓	✓		✓
	Potting soil / growing media / substrates for ornamental plants	B-10		✓	<> 20%		75%	25%	Must not be used to grow plants that are used for food or feed production. Life cycle data and statistics must prove that the end of life is in soil (e.g., via composting) for a relevant share of the total volume produced. This share defines the security margin.	✓		✓	✓	✓			✓	✓		✓

Origin	Matrix	ID	Controlling period in years	Diffuse C-sink authorized	Leakage margin to be deduced before registration	C remaining during temporary C-sink	C remaining after > 1000 y	SPC fraction with MRT of 50 years	Conditions	EBC-FeedPlus	EBC-Feed	EBC-AgroOrganic	EBC-Agro	EBC-Urban	EBC-Consumer-Materials	EBC-BasicMaterials	WBC Premium	WBC Agro	WBC Materials	Global Artisan C-Sink	
Mineral Matrix	Concrete	Min-01	30 years for the first period, then every 10 years.			100%	75%	25%	After biochar addition, these matrixes must not be subject to thermal treatment beyond drying. Following demolition, the biochar- containing mineral matrix should be recycled for use in new building materials or as gravel for road construction or landscaping to preserve the matrix. In the case of Global Material C-sink certified constructions, demolition must be communicated to the Global C-Sink Registry so that the registered matrix and geolocation can be modified accordingly. The certifier establishes a controlling period for the construction, which is monitored by satellite imagery. If the construction is removed or significantly altered without proper notification to the registry, the C-sink certification will be revoked.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Cement, cement mortar	Min-02		✓		100%	75%	25%		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Lime, lime mortar, gypsum	Min-03		✓		100%	75%	25%		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Clay, clay plaster, mud-bricks and clay drywall	Min-04		✓		100%	75%	25%		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Asphalt	Min-05				100%			Lost of pyrogenic carbon during the different recycling process are not yet investigated. Currently 80% of asphalt is recycled at temperatures that do not cause biochar degradation (< 300 °C). However, pending the results of those investigations, a control period of 30 years is set. Pyrolysis treatment of used asphalt causes the removal from the C-sink register.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Materials	Composite	Mat-01	individual	✓		100%			The temporary C-sink period depends on the expected life span of each respective product or product class and expected recycling pathways determined by statistics. It is governed by the Global Material C-Sink standard. High security margins are due to variation between use scenarios and difficulty of tracking and control.						✓		✓		✓		
	Plastics	Mat-03	individual	✓		100%									✓		✓		✓		
	Textiles	Mat-04	individual	✓		100%									✓		✓		✓		
	Paints	Mat-05	individual	✓		100%									✓		✓		✓		
Soil	Agricultural soil	S-01		✓			75%	25%	Tracking and prove of soil application must be provided. Wetlands (S 04) must be excluded.	✓		✓	✓				✓	✓		✓	
	Urban soil	S-02		✓			75%	25%	Tracking or reporting and prove of soil application must be provided.	✓	✓	✓	✓	✓			✓	✓		✓	
	Mine reclamation	S-03					75%	25%	Tracking or reporting and prove of soil application must be provided.	✓		✓	✓				✓	✓			
	Wet lands	S-04	✓		100%		75%	25%	Biochar may lead to accelerated mineralization of wetlands. Too few scientific data available. Not accepted as C-sink matrix today.	not allowed as C-Sink Matrix (yet)						not allowed as C-Sink Matrix (yet)					
	Forest	S-05			0-20%		75%	25%	Biochar may lead to accelerated mineralization of certain boreal forests where a higher security margin is applied. The soil of natural forests should better not be disturbed by machines and substrates. The safety margin can be reduced to zero if the soil is proven to be degraded with a low SOC content or if the biochar is used as a concentrated root zone application during planting.	✓		✓	✓				✓	✓		✓	
	Foundation and compacted ground under constructions (e.g. road-beds)	S-06					75%	25%	Depending on the subsoil analysis (SOC) and depth, reduced degradation of SPC can be expected but not yet guaranteed. Once sufficient scientific data are provided, a correction of the SPC degradation can be registered retroactively.	✓	✓	✓	✓	✓			✓	✓			
	Clay subsoil	S-07					75%	25%	Depending on the clay-soil analysis (SOC) and depth, reduced degradation of SPC can be expected but not yet guaranteed. Once sufficient scientific data are provided, a correction of the SPC degradation can be registered retroactively.	✓	✓	✓	✓	✓			✓	✓			
	Sediments	S-08					75%	25%	Depending on the sediment analysis (SOC), depth, and location, reduced degradation of SPC can be expected but not yet guaranteed. Once sufficient scientific data are provided, a correction of the SPC degradation can be registered retroactively.	✓	✓	✓	✓				✓	✓			

Origin	Matrix	ID	Controlling period in years	Diffuse C-sink authorized	Leakage margin to be deduced before registration	C remaining during temporary C-sink	C remaining after > 1000 y	SPC fraction with MRT of 50 years	Conditions	EBC-FeedPlus	EBC-Feed	EBC-AgroOrganic	EBC-Agro	EBC-Urban	EBC-Consumer-Materials	EBC-BasicMaterials	WBC Premium	WBC Agro	WBC Materials	Global Artisan C-Sink
Landfill	Waste disposal	LF-01					75%	25%	Only authorized when mixed to cover soil or any other mineral matrix at a ratio < 1:5 to avoid any risk of smoldering.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Ash	LF-02					75%	25%	If the biochar is homogeneously mixed to pyrolysis ash at a ratio < 1 : 1.5, the biochar is efficiently protected from biological or chemical oxidation when applied to a landfill even in cases of landfill fire. The biochar persistence can thus be certified as for biochar soil application.The biochar-ash must be certified at least as EBC- or WBC-Materials.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Waste water	Waste water treatment / Sewage Sludge	W-05		✓	10%		75%	25%	Tracking of the treatment and sludge needed to exclude that the amended sludge ends up as feedstock for pyrolysis or combustion. The margin was set as the sludge amendment and use is sometimes obscured.	✓		✓	✓				✓	✓		✓
Geological storage		G-01			5%		100%	0%	Geological storage requires application deep below the soil in geological horizons, where no biological activity is sustained, protected from water and air, and where it cannot be recovered because of a sealed cover or because of its embedding in a C-sink matrix. For storages above 10,000 m³ continous monitoring of temperature and gas evolution must be set up.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	

* The use of biochar with certification class EBC-Urban in the biological substrates is only permitted when the substrate packaging indicates that it is for urban use only and must not be used for agricultural/horticultural purposes.

SPC = semi-persistent carbon fraction of biochar

For the inclusion of other matrices not included yet in the present positive list an official request can be sent to Carbon Standards.

The decision about the inclusion in the positive list as well as possible additional requirements will be made by the scientific advisory board of Carbon Standards. All decisions are justified and published on the Carbon Standard website.

Regulation by Matrix Types

Biological Matrices

- For products with a clear application recommendation on the label (e.g., fertilizer or feed additive), this recommendation is sufficient as evidence of diffuse application.
- For intermediate products (e.g., use in biogas plants), documentation must provide that the matrix will ultimately end up in a soil-based application.

Mineral Matrices

- Once biochar has been incorporated into the matrix, the carbon sink can be registered as a diffuse carbon sink.
- Important: If the biochar is intended to be used under the Construction C-sink Standard, it must be tracked through to the building.

Materials

- Tracking up to the point of application is sufficient.
- Further tracking is voluntary but recommended.

Geolocation Requirement:

Geolocation is mandatory for the following cases:

- Direct soil application of biochar,
- Landfilling,
- Geological storage,
- Wastewater treatment (in this case, it must additionally be documented that the matrix will ultimately end up in a soil-based application).

Note:

- If the biochar is already embedded in a biological matrix (e.g., feed, fermentation residues) and is applied according to dosage recommendations, it is considered a diffuse sink – even in the case of later soil application.
- Unprocessed biochar can also be recognized as incorporated into a matrix if the First C-sink Owner provides annual proof that there is no risk of alternative use other than soil application.

This means:

- There is no economic incentive to apply the biochar differently, since its price is significantly higher than the market price for charcoal. For this, detailed knowledge of the group of recipients and their fields of activity is required.
- The delivery note can be combined with this documentation and serves as proof of incorporation into the matrix.